

Overview

HP 240 G7 Notebook PC



1. Webcam LED
2. Webcam
3. Internal microphone
4. Touchpad
5. Touchpad button
6. Power indicator LED

Left

7. Hard drive indicator LED
8. SD Card slot
9. USB 2.0 port
10. Security lock slot (Lock sold separately)
11. Power button

Overview



- 1. AC Smart Pin adapter plug
- 2. RJ-45/Ethernet port
- 3. HDMI port (Cable not included)

Right

- 4. USB 3.1 Gen 1 port
- 5. USB 3.1 Gen 1 port
- 6. Audio combo jack

At A Glance

Overview

- Preinstall with Windows 10 versions, FreeDOS or Ubuntu
- Choice of 8th or 7th Generation Intel® Core™, Intel® Pentium®, or Intel® Celeron® processors
- 14" (35.56 cm) diagonal HD Anti-Glare Display
- Choice of Integrated Intel® UHD Graphics 620, HD Graphics 620, UHD Graphics 605, UHD Graphics 600 Graphics or Switchable Discrete Graphics AMD Radeon™ 520
- Dark Ash Silver color with texture pattern
- Up to 1 TB Hard Drive or 256 GB M.2 PCIe Value Solid State Drive
- Weight starting at 1.52 kg (3.4 lbs)
- Security features including FW TPM 2.0 and security lock slot (Lock not included)
- Full size textured island-style keyboard
- Touchpad with gestures support
- HP webcam with single digital microphone and HD (supporting WDR- Wide Dynamic Range) or VGA camera
- Two USB 3.1 (Gen 1) ports and One USB 2.0 port
- Wireless LAN (WLAN) up to 802.11ac to keep you connected
- Up to 12 hours 15 mins (Intel® 7th generation CPU, HD display, Solid State Drive & 3-cell 41 WHr battery)

NOTE: See important legal disclosures for all listed specs in their respective features sections.

Features

PRODUCT NAME

HP 240 G7 Notebook PC

OPERATING SYSTEM

Preinstalled	Windows 10 Pro 64 ¹
	Windows 10 Home 64 ¹
	Windows 10 Home Single Language 64 ¹
	Windows 10 Pro 64 (National Academic only) ^{1,2}
	FreeDOS
	Ubuntu

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com/>.

2. Some devices for academic use will automatically be updated to Windows 10 Pro Education with the Windows 10 Anniversary Update. Features vary; see <https://aka.ms/ProEducation> for Windows 10 Pro Education feature information.

PROCESSOR

Intel® Core™ i7-8565U processor with Intel® UHD Graphics 620 (1.8 GHz base frequency, up to 4.6 GHz with Intel® Turbo Boost Technology, 8 MB cache, 4 cores)^{3,4,5,6}

Intel® Core™ i5-8265U with Intel® UHD Graphics 620 Graphics (1.6 GHz base frequency, up to 3.9 GHz with Intel® Turbo Boost Technology, 6 MB L3 cache, 4 cores)

Intel® Core™ i7-8550U with Intel® UHD graphics 620 (1.8 GHz base frequency, up to 4 GHz with Intel® Turbo Boost Technology, 8 MB cache, 4 cores)^{3,4,5,6}

Intel® Core™ i5-8250U with Intel® UHD Graphics 620 (1.6 GHz base frequency, up to 3.4 GHz with Intel® Turbo Boost Technology, 6 MB cache, 4 cores)^{3,4,5,6}

Intel® Core™ i3-7020U with Intel® HD Graphics 620 (2.3 GHz, 3 MB cache, 2 cores)^{3,4,6}

Intel® Pentium® Silver Processor N5000 with Intel® UHD Graphics 605 (1.1 GHz base frequency, up to 2.7 GHz burst frequency, 4 MB cache, 4 cores)^{3,4,6}

Intel® Celeron® Processor N4000 with Intel® UHD Graphics 600 (1.1 GHz base frequency, up to 2.6 GHz burst frequency, 4 MB cache, 2 cores)^{3,4,6}

Processor Family

8th Generation Intel® Core™ i7 processor (i7-8565U, i7-8550U)⁶

8th Generation Intel® Core™ i5 processor (i5-8265U, i5-8250U)⁶

7th Generation Intel® Core™ i3 processor (i3-7020U)⁶

Intel® Pentium® processor (N5000 is Windows 10 only)⁶

Intel® Celeron® processor (N4000 is Windows 10 only)⁶

Features

3. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.
 4. Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.
 5. Intel® Turbo Boost performance varies depending on hardware, software and overall system configuration. See <http://www.intel.com/technology/turboboost> for more information.
 6. In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on <http://www.support.hp.com>.
-

CHIPSET

Intel® SOC Chipset

GRAPHICS

Integrated

Intel® UHD Graphics 620⁷
Intel® HD Graphics 620⁷
Intel® UHD Graphics 605⁷
Intel® UHD Graphics 600⁷

Discrete

AMD Radeon™ RX 520 (2 GB GDDR5 dedicated)⁸

Supports

Support HD decode, DX12, HDMI 1.4b⁹

7. HD content required to view HD images.
 8. AMD Dynamic Switchable Graphics technology requires an Intel processor, plus an AMD Radeon™ discrete graphics configuration and is not available on FreeDOS and Linux OS. With AMD Dynamic Switchable Graphics technology, full enablement of all discrete graphics video and display features may not be supported on all systems (e.g. OpenGL applications will run on the integrated GPU or the APU as the case may be).
 9. HDMI cable sold separately.
-

DISPLAY

Features

Internal

Non-Touch

35.56 cm (14") diagonal HD SVA eDP anti-glare WLED-backlit slim-flat, 220 cd/m², 45% NTSC (1366 x 768)^{7,10}

HDMI

Port supports resolutions up to 1920 x 1200 external resolution @60 Hz

7. HD content required to view HD images.

10. Resolutions are dependent upon monitor capability, and resolution and color depth settings.

STORAGE AND DRIVES

Primary Storage

1 TB 5400 rpm SATA¹¹

500 GB 7200 rpm SATA¹¹

500 GB 5400 rpm SATA¹¹

Primary M.2 Storage

128 GB M.2 SATA-3 TLC Solid State Drive¹¹

256 GB M.2 SATA-3 TLC Solid State Drive¹¹

256 GB PCIe® NVMe™ M.2 Value Solid State Drive¹¹

11. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10) is reserved for system recovery software.

MEMORY

Features

Standard

Maximum Memory

16 GB DDR4-2400 SDRAM ¹²

16 GB DDR4-2133 SDRAM ¹²

Memory

16 GB DDR4-2400 SDRAM (2 X 8 GB)¹²

12 GB DDR4-2400 SDRAM (4 GB + 8 GB)¹²

8 GB DDR4-2400 SDRAM (1 x 8 GB)

8 GB DDR4-2400 SDRAM (2 x 4 GB)¹²

4 GB DDR4-2400 SDRAM (1 x 4 GB)

16 GB DDR4-2133 SDRAM (2 X 8 GB)¹²

12 GB DDR4-2133 SDRAM (4 GB + 8 GB)¹²

8 GB DDR4-2133 SDRAM (1 x 8 GB)

8 GB DDR4-2133 SDRAM (2 x 4 GB)¹²

4 GB DDR4-2133 SDRAM (1 x 4 GB)

Memory Slots

2 SODIMM (Intel® 8th & 7th Generation Intel® Core™ processor)

DDR4 PC4 SODIMMS, system runs at 2400 (Intel 7th Gen (KBL) runs at 2133)

Supports Dual Channel Memory

1 SODIMM (Intel® Pentium®, Celeron® processors)

All slots are customer non-accessible / non-upgradeable

NOTE: All slots are customer non-accessible / non-upgradeable.

12. Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

NETWORKING/COMMUNICATIONS

Features

WLAN

Realtek 802.11ac (2x2) WLAN and Bluetooth® 4.2 Combo (MU-MIMO supported)¹³

Realtek 802.11ac (1x1) WLAN and Bluetooth® 4.2 Combo (MU-MIMO supported)¹³

Realtek 802.11b/g/n (1x1) and Bluetooth® 4.2 Combo¹³

Miracast

Compatible with Miracast-certified devices ¹⁴

Ethernet

Integrated 10/100/1000 GbE NIC ¹⁵

13. Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited.

14. Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming.

15. The term "10/100/1000" or "Gigabit" Ethernet indicates compatibility with IEEE standard 802.3ab for Gigabit Ethernet, and does not connote actual operating speed of 1 Gb/s. For high-speed transmission, connection to a Gigabit Ethernet server and network infrastructure is required.

AUDIO/MULTIMEDIA

Audio

2 Integrated stereo speakers

Camera

HP TrueVision HD Camera ^{7,16}

Webcam

VGA webcam ^{16,17}

7. HD content required to view HD images.

16. Sold separately or as an optional feature.

17. Internet access required.

KEYBOARDS/TOUCHPAD

Features

Keyboard

Full size island-style keyboard

Pointing Device

Touchpad with multi-touch gesture support

Function Keys

F1 - Open "How to get help in Windows 10" webpage

F2 - Brightness Down

F3 - Brightness Up

F4 - Display Switching

F5 - Blank

F6 - Mute

F7 - Volume Down

F8 - Volume Up

F9 - Previous

F10 - Play/Pause

F11 - Next

F12 - Airplane mode

SOFTWARE AND SECURITY

Preinstalled Software

HP JumpStart

HP Documentation

HP Setup Integrated OOBE

HP SSRM

HP Audio Switch

HP Support Assistant ¹⁸

McAfee LiveSafe™

Security Management

TPM 2.0¹⁹

Security lock slot (Lock sold separately)

¹⁸. HP Support Assistant requires Windows and Internet access.

¹⁹. Firmware TPM is version 2.0. Hardware TPM is v1.2, which is a subset of the TPM 2.0 specification version v0.89 as implemented by Intel Platform Trust Technology (PTT).

POWER

Features

Power Supply

HP Smart 65 W External AC power adapter ^{20,22}
HP Smart 65 W EM External AC power adapter ^{20,22}
HP Smart 45 W External AC power adapter ²⁰

Primary Battery

HP Long Life 3-cell, 41 Wh Li-ion ²¹
Support battery fast charging - Approximately 90% in 90 minutes²²

Battery Life

Up to 12 hours 15 mins (Intel® 7th generation CPU, HD display, Solid State Drive & 3-cell 41 WHr battery) ²³

Power Cord

1M (3.28 feet) length power cord

Battery Weight

0.18 kg
0.39 lb

20. Availability may vary by country.

21. Battery is internal and not replaceable by customer. Serviceable by warranty.

22. Recharges the battery up to 90% within 90 minutes when the system is off or in standby mode. Power adapter with a minimum capacity of 65 watts is required. After charging has reached 90% capacity, charging will return to normal. Charging time may vary +/- 10% due to System tolerance.

23. Windows 10 MM14 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See <http://www.bapco.com> for additional details.

WEIGHTS & DIMENSIONS

Product Weight

Starting at 3.3 lbs²⁴
Starting at 1.52 kg²⁴

Product Dimensions (W x D x H)

13.19 x 9.21 x 0.78 in
33.5 x 23.4 x 1.99 cm

24. Weight will vary by configuration.

PORTS/SLOTS

Features

Ports/Connectors

- 2 USB 3.1 Gen 1
- 1 USB 2.0
- 1 HDMI v1.4b⁹
- 1 RJ-45
- 1 AC power
- 1 Headphone/microphone combo jack

Expansion Slots

- 1 multi-format digital media reader
- Supports SD, SDHC, SDXC

9. HDMI cable sold separately.

SERVICE AND SUPPORT

HP Services offers 1-year limited warranties and 90 day software limited warranty options depending on country. Batteries have a default one year limited warranty except for Long Life batteries which will have same 1-year or 3-year limited warranty as the platform. Refer to <http://www.hp.com/support/batterywarranty/> for additional battery information. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: <http://www.hp.com/go/cpc>.²⁵

25. HP Care Packs are sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit <http://www.hp.com/go/cpc>. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.

Technical Specifications

SYSTEM UNIT

Stand-Alone Power Requirements

(AC Power)

Nominal Operating Voltage	19.5 V
Average Operating Power	Win 10
Integrated graphics	7.69W
Max Operating Power	Discrete < 65W UMA < 45W

Temperature

Operating	32° to 95° F (0° to 35° C) (not writing optical) 41° to 95° F (5° to 35° C) (writing optical)
Non-operating	-4° to 140° F (-20° to 60° C)

Relative Humidity

Operating	10% to 90%, non-condensing
Non-operating	5% to 95%

Shock

Operating	40 G, 2 ms duration, half-sine
Non-operating	240 G, 2 ms duration, half-sine

Random Vibration

Operating	1.043 grms
Non-operating	3.5 grms

Planned Industry Standard Certifications

UL	Yes
CSA	No
FCC Compliance	Yes
ENERGY STAR®	Yes ²⁶
EPEAT® 2019	Yes, Silver in U.S. ²⁷
ICES	Yes
Australia /	Yes
NZ A-Tick Compliance	Yes
CCC	Yes
Japan VCCI Compliance	Yes
KC	Yes
BSMI	Yes
CE Marking Compliance	Yes
BNCI or BELUS	Yes
CIT	Yes
GOST	Yes
Saudi Arabian Compliance (ICCP)	Yes
SABS	Yes

26. Configurations of the HP 240 G7 that are ENERGY STAR® certified² are identified as HP 240 G7 ENERGY STAR on HP websites and on <http://www.energystar.gov>.

27. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. Status varies by country. Visit

Technical Specifications

<http://www.epeat.net> for more information.

DISPLAYS

14" HD WLED Anti-Glare diagonal (1366 x 768) slim-flat (3.0mm), SVA, eDP	Outline Dimensions (W x H x D)	320.9 x 250.6 x 3.0
	Active Area	309.5 x 174.05
	Weight	270g max
	Diagonal Size	14.0 (inch)
	Thickness	3.0 (mm) max
	Interface	eDP 1.2
	Surface Treatment	AG
	Contrast Ratio	600:1 (typ. AG)
	Refresh Rate	60Hz
	Brightness	220nits typical
	Pixel Resolution	1366 x 768 (HD)
	Format of LCD Pixel Arrangement	RGB
	Backlight	LED
	Color Gamut Coverage	45% of NTSC
	Color Depth	6 bits
	Viewing Angle	45/45/20/40

STORAGE AND DRIVES

500 GB 5400 rpm SATA Dard Drive	Drive Weight	92g(0.20lb)
	Rotation speed	5400 rpm
	Cache Buffer	Up to 128MB
	Height	7.0 +/- 0.2 mm (0.28 +/- .008 in)
	Width	69.85 +/- 0.25 mm (2.750 +/- 0.010 in)
	Interface	ATA-8, SATA 3.0
	Transfer Rate	600 MB/s
	Seek Time	Single Track: 2 ~ 1.5 ms Average: 11 ~ 16 ms Maximum: 18 ~ 22 ms
	Logical Blocks	976,773,168
	Operating Temperature	0° to 60°C
	Security Features	ATA Security
	Features	S.M.A.R.T., NCQ, Ultra DMA

Technical Specifications

500 GB 7200 rpm SATA Hard Drive	Drive Weight	92g(0.20lb)
	Rotation speed	7200 rpm
	Cache Buffer	Up to 128MB
	Height	7.0 +/- 0.2 mm (0.28 +/- .008 in)
	Width	69.85 +/- 0.25 mm (2.750 +/- 0.010 in)
	Interface	ATA-8, SATA 3.0
	Transfer Rate	Single Track: 2 ~ 1.5 ms; Average: 11 ~ 13 ms; Maximum: 18 ~ 22 ms
	Seek Time	976,773,168
	Logical Blocks	0° to 60°C
	Operating Temperature	ATA Security
	Security Features	S.M.A.R.T., NCQ, Ultra DMA
1 TB 5400 rpm SATA Hard Drive	Drive Weight	90g(0.198lb)
	Rotation speed	5400 rpm
	Cache Buffer	Up to 128MB
	Height	<7.2mm
	Width	69.85 +/- 0.25 mm (2.750 +/- 0.010 in)
	Interface	ATA-8, SATA 3.0
	Transfer Rate	600 MB/s
	Seek Time	Single Track: 2 ~ 1.5 ms; Average: 11 ~ 16 ms; Maximum: 18 ~ 22 ms
	Logical Blocks	976,773,168
	Operating Temperature	0° to 60°C
	Security Features	ATA Security
128 GB 2280 M2 SATA-3 TLC Solid State Drive	Drive Weight	0.02 lb (10 g)
	NAND Type/Size	TLC/128GB
	Height	0.09 in (2.3 mm)
	Width	0.87 in (22 mm)
	Interface	ATA-8, SATA 3.0
	Transfer Rate	550MB/s
	Logical Blocks	250,069,680
	Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
	Security Features	ATA Security
	Features	DIPM; TRIM; DEVSLP

Technical Specifications

256 GB 2280 M2 SATA-3 TLC Solid State Drive	Drive Weight	0.02 lb (10 g)
	Height	0.09 in (2.3 mm)
	Width	0.87 in (22 mm)
	Interface	ATA-8, SATA 3.0
	Transfer Rate	550MB/s
	Logical Blocks	500,118,192
	Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
	Security Features	ATA Security
	Features	DIPM; TRIM; DEVSLP

256 GB 2280 M2 PCIe NVMe Value Solid State Drive	Form Factor	M.2 2280
	Capacity	256 GB
	NAND Type	TLC
	Height	0.09 in (2.3 mm)
	Width	0.87 in (22 mm)
	Weight	0.01 lb (6 g) ~ 0.02 lb (10 g)
	Interface	PCIe NVMe Gen3x2
	Maximum Sequential Read	Up To 1500 MB/s
	Maximum Sequential Write	Up To 1000 MB/s
	Logical Blocks	500,118,192
	Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
	Features	DIPM; TRIM; DEVSLP

16 GB Intel Optane Solution PCIe Gen3x2 M.2 SSD	Form Factor	M.2 2280
	Capacity	16 GB
	NAND Type	3D Xpoint
	Height	0.09 in (2.3 mm)
	Width	0.87 in (22 mm)
	Interface	PCIe NVMe Gen3x2
	Maximum Sequential Read	1350MB/s
	Maximum Sequential Write	290MB/s
	Logical Blocks	31,257,387
	Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]

NETWORKING/COMMUNICATIONS

WLAN

Realtek RTL8822BE 802.11 ac 2x2 WLAN and Bluetooth® 4.2 Combo Adapter (MU-	Wireless LAN Standards	IEEE 802.11a
		IEEE 802.11b
		IEEE 802.11g

Technical Specifications

MIMO supported)

	IEEE 802.11n IEEE 802.11ac
Interoperability	Wi-Fi® certified
Frequency Band	802.11b/g/n <ul style="list-style-type: none"> • 2.402 - 2.482 GHz 802.11a/n <ul style="list-style-type: none"> • 4.9 - 4.95 GHz (Japan) • 5.15 - 5.25 GHz • 5.25 - 5.35 GHz • 5.47 - 5.725 GHz • 5.825 - 5.850 GHz
Data Rates	<ul style="list-style-type: none"> • 802.11b: 1, 2, 5.5, 11 Mbps • 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz) • 802.11ac: MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, and 80MHz)
Modulation	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM
Security³	<ul style="list-style-type: none"> • IEEE and WiFi® compliant 64 / 128 bit WEP encryption for a/b/g mode only • AES-CCMP: 128 bit in hardware • 802.1x authentication • WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. • WPA2 certification • IEEE 802.11i • Cisco Certified Extensions, all versions through CCX4 and CCX Lite • WAPI
Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power²	<ul style="list-style-type: none"> • 802.11b: +14dBm minimum • 802.11g: +12dBm minimum • 802.11a: +12dBm minimum • 802.11n HT20(2.4GHz): +12dBm minimum • 802.11n HT40(2.4GHz): +12dBm minimum • 802.11n HT20(5GHz): +10dBm minimum • 802.11n HT40(5GHz): +10dBm minimum • 802.11ac VHT80(5GHz): +10dBm minimum
Power Consumption	Transmit mode: 2.0 W Receive mode: 1.6 W Idle mode (PSP) 180 mW (WLAN Associated) Idle mode: 50 mW (WLAN unassociated) Connected Standby/Modern Standby: 10mW Radio disabled: 8 mW

Technical Specifications

Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
Receiver Sensitivity³	802.11b, 1Mbps: -93.5dBm maximum 802.11b, 11Mbps: -84dBm maximum 802.11a/g, 6Mbps: -86dBm maximum 802.11a/g, 54Mbps: -72dBm maximum 802.11n, MCS07: -67dBm maximum 802.11n, MCS15: -64dBm maximum 802.11ac, MCS0: -84dBm maximum 802.11ac, MCS9: -59dBm maximum
Antenna type	High efficiency antenna with spatial diversity, mounted in the display enclosure Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
Form Factor	PCI-Express M.2 MiniCard
Dimensions	Type 2230: 2.3 x 22.0 x 30.0 mm
Weight	Type 2230: 2.8g
Operating Voltage	3.3v +/- 9%
Temperature	Operating 14° to 158° F (-10° to 70° C) Non-operating -40° to 176° F (-40° to 80° C)
Humidity	Operating 10% to 90% (non-condensing) Non-operating 5% to 95% (non-condensing)
Altitude	Operating 0 to 10,000 ft (3,048 m) Non-operating 0 to 50,000 ft (15,240 m)
LED Activity	LED Amber - Radio OFF; LED White - Radio ON

1. Check latest software/driver release for updates on supported security features.
2. Maximum output power may vary by country according to local regulations.
3. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

HP Integrated Module with Bluetooth 4.0/4.1/4.2 Wireless Technology

Bluetooth® Specification	4.0/4.1/4.2 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy: 0~79 (1 MHz/CH) BLE: 0~39 (2 MHz/CH)
Signaling Data Rate	Legacy: 3 Mbps Signaling data rate ¹ BLE: 1 Mbps Signaling data rate ¹

1. Actual throughput may vary.

Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice channels

Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)

Technical Specifications

Transmit Power		The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.
Realtek RTL8723DE 802.11 bgn (1x1) WLAN and Bluetooth® 4.2 Combo Adapter	Wireless LAN Standards	IEEE 802.11b IEEE 802.11g IEEE 802.11n
	Interoperability	Wi-Fi® certified
	Frequency Band	802.11b/g/n
	Data Rates	<ul style="list-style-type: none"> 2.402 - 2.482 GHz 802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: MCS 0 ~ MCS 7, (20MHz, and 40MHz)
	Modulation	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM
	Security³	<ul style="list-style-type: none"> IEEE and WiFi® compliant 64 / 128 bit WEP encryption for a/b/g mode only AES-CCMP: 128 bit in hardware 802.1x authentication WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. WPA2 certification IEEE 802.11i Cisco Certified Extensions, all versions through CCX4 and CCX Lite WAPI
	Network Architecture Models	Ad-hoc (Peer to Peer) Infrastructure (Access Point Required)
	Roaming	IEEE 802.11 compliant roaming between access points
	Output Power²	<ul style="list-style-type: none"> 802.11b: +14dBm minimum 802.11g: +12dBm minimum 802.11n HT20(2.4GHz): +12dBm minimum 802.11n HT40(2.4GHz): +12dBm minimum
	Power Consumption	<ul style="list-style-type: none"> Transmit mode 2.0 W Receive mode 1.6 W Idle mode (PSP)180 mW (WLAN Associated) Idle mode 50 mW (WLAN unassociated) Connected Standby 10mW Radio disabled 8 mW
	Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
	Receiver Sensitivity³	802.11b, 1Mbps: -93.5dBm maximum 802.11b, 11Mbps: -84dBm maximum 802.11g, 6Mbps: -86dBm maximum 802.11g, 54Mbps: -72dBm maximum 802.11n, MCS07: -67dBm maximum

Technical Specifications

Antenna type	High efficiency antenna.	
	One embedded dual band 2.4/5 GHz antenna is provided to the card to support WLAN communications and Bluetooth communications	
Form Factor	PCI-Express M.2 MiniCard	
Dimensions	Type 2230: 2.3 x 22.0 x 30.0 mm	
Weight	Type 2230: 2.8g	
Operating Voltage	3.3v +/- 9%	
Temperature	Operating	14° to 158° F (-10° to 70° C)
	Non-operating	-40° to 176° F (-40° to 80° C)
Humidity	Operating	10% to 90% (non-condensing)
	Non-operating	5% to 95% (non-condensing)
Altitude	Operating	0 to 10,000 ft (3,048 m)
	Non-operating	0 to 50,000 ft (15,240 m)
LED Activity	LED Amber - Radio OFF; LED White - Radio ON	

- 1. Check latest software/driver release for updates on supported security features.
- 2. Maximum output power may vary by country according to local regulations.
- 3. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

HP Integrated Module with Bluetooth 4.0/4.1/4.2 Wireless Technology

Bluetooth® Specification	4.0/4.1/4.2 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy: 0~79 (1 MHz/CH)
	BLE: 0~39 (2 MHz/CH)
Signaling Data Rate	Legacy: 3 Mbps Signaling data rate ¹
	BLE: 1 Mbps Signaling data rate ¹

- 1. Actual throughput may vary.

Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice channels

Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)

Transmit Power	The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.
----------------	---

Technical Specifications

**ac 1x1 WLAN and Bluetooth®
4.2 Combo Adapter (MU-
MIMO supported)**

	IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac
Interoperability	Wi-Fi® certified
Frequency Band	802.11b/g/n <ul style="list-style-type: none"> • 2.402 - 2.482 GHz 802.11a/n <ul style="list-style-type: none"> • 4.9 - 4.95 GHz (Japan) • 5.15 - 5.25 GHz • 5.25 - 5.35 GHz • 5.47 - 5.725 GHz • 5.825 - 5.850 GHz
Data Rates	<ul style="list-style-type: none"> • 802.11b: 1, 2, 5.5, 11 Mbps • 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps • 802.11n: MCS 0 ~ MCS 15, (20MHz, and 40MHz) • 802.11ac: MCS0 ~ MCS9, (1SS, and 2SS) (20MHz, 40MHz, and 80MHz)
Modulation	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM
Security³	<ul style="list-style-type: none"> • IEEE and WiFi® compliant 64 / 128 bit WEP encryption for a/b/g mode only • AES-CCMP: 128 bit in hardware • 802.1x authentication • WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. • WPA2 certification • IEEE 802.11i • Cisco Certified Extensions, all versions through CCX4 and CCX Lite • WAPI
Network Architecture	Ad-hoc (Peer to Peer)
Models	Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power²	<ul style="list-style-type: none"> • 802.11b: +14dBm minimum • 802.11g: +12dBm minimum • 802.11a: +12dBm minimum • 802.11n HT20(2.4GHz): +12dBm minimum • 802.11n HT40(2.4GHz): +12dBm minimum • 802.11n HT20(5GHz): +10dBm minimum • 802.11n HT40(5GHz): +10dBm minimum • 802.11ac VHT80(5GHz): +10dBm minimum
Power Consumption	<ul style="list-style-type: none"> • Transmit mode 2.0 W • Receive mode 1.6 W • Idle mode (PSP) 180 mW (WLAN Associated) • Idle mode 50 mW (WLAN unassociated)

Technical Specifications

	<ul style="list-style-type: none">• Connected Standby 10mW• Radio disabled 8 mW	
Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode	
Receiver Sensitivity ³	802.11b, 1Mbps: -93.5dBm maximum 802.11b, 11Mbps: -84dBm maximum 802.11a/g, 6Mbps: -86dBm maximum 802.11a/g, 54Mbps: -72dBm maximum 802.11n, MCS07: -67dBm maximum 802.11n, MCS15: -64dBm maximum 802.11ac, MCS0: -84dBm maximum 802.11ac, MCS9: -59dBm maximum	
Antenna type	High efficiency antenna. One embedded dual band 2.4/5 GHz antenna is provided to the card to support WLAN communications and Bluetooth communications	
Form Factor	PCI-Express M.2 MiniCard	
Dimensions	Type 2230: 2.3 x 22.0 x 30.0 mm	
Weight	Type 2230: 2.8g	
Operating Voltage	3.3v +/- 9%	
Temperature	Operating	14° to 158° F (-10° to 70° C)
	Non-operating	-40° to 176° F (-40° to 80° C)
Humidity	Operating	10% to 90% (non-condensing)
	Non-operating	5% to 95% (non-condensing)
Altitude	Operating	0 to 10,000 ft (3,048 m)
	Non-operating	0 to 50,000 ft (15,240 m)
LED Activity	LED Amber - Radio OFF; LED White - Radio ON	
<p>1. Check latest software/driver release for updates on supported security features.</p> <p>2. Maximum output power may vary by country according to local regulations.</p> <p>3. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).</p>		

HP Integrated Module with Bluetooth 4.0/4.1/4.2 Wireless Technology

Bluetooth® Specification	4.0/4.1/4.2 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy: 0~79 (1 MHz/CH) BLE: 0~39 (2 MHz/CH)
Signaling Data Rate	Legacy: 3 Mbps Signaling data rate ¹ BLE: 1 Mbps Signaling data rate ¹
<p>1. Actual throughput may vary.</p> <p>Legacy: Synchronous Connection Oriented links up to 3, 64 kbps, voice channel</p> <p>Legacy: Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)</p>	

Technical Specifications

	Transmit Power	The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.
Realtek Ethernet (10/100/1000)	Ethernet Features	10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14) 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30) 1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 8023 clauses 40) Auto-Negotiation (Automatic Speed Selection) Full Duplex Operation at all Speeds, Half Duplex operation at 10 and 100 Mbit/s IEEE 802.1p QoS (Quality of Service) Support IEEE 802.1q VLAN support IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable) IEEE 802.3az EEE (Energy Efficient Ethernet) Jumbo Frame 9K Auto MDI/MDIX Crossover cable detection
	Power Management	ACPI compliant - multiple power modes Situation-sensitive features reduce power consumption Advanced link down power saving for reducing link down power consumption
	Performance Features	TCP/IP/UDP Checksum Offload (configurable) Protocol Offload (ARP & NS) Large send offload and Giant send offload Receiving Side Scaling
	Manageability	Wake-on-LAN from standby and hibernation (Magic Packet and Microsoft Wake Frame); Wake-on-LAN from off (Magic Packet only) PXE 2.1 Remote Boot Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30) Comprehensive diagnostic and configuration software suite Virtual Cable Doctor for Ethernet cable status
	Interface	PCI Express 1.1 to support ASPM L1
	NIC Device Driver Name	Realtek PCIe GBE Ethernet Family Controller

POWER

Technical Specifications

HP 65W Smart AC adapter	Dimensions (H x W x D)	108 x 47 x 37.4mm
	Weight	250 g
	Input	100 to 240 VAC
	Input Efficiency	88.0 % at 115 VAC and 89.0 % at 230VAC
	Input frequency range	50~ 60 Hz
	Input AC current	Max. 1.7 A at 90 VAC
	Output	
	Output power	65W
	DC output	19.5V
	Hold-up time	5ms at 115 VAC input
	Output current limit	The power supply shall limit the maximum steady state output current to an average current of 11 Amperes.
	Connector	4.5mm Barrel Type,
	Environmental Design	
	Operating temperature	32°F to 95°F (0°C to 35° C)
45 W AC adapter	Non-operating (storage) temperature	-4°F to 185°F (-20°C to 85°C)
	Altitude	-4°F to 185°F (-20°C to 85°C)
	Humidity	The power supply can be operated at 5,000 m above sea level
	Storage Humidity	
	EMI and Safety Certifications	*CE Mark - full compliance with LVD and EMC directives * Worldwide safety standards - IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals - C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. * MTBF - over 200,000 hours at 25°C ambient condition.
	Dimensions (H x W x D)	95 x 40 x 26.5mm
	Weight	200 g
	Input	100 to 240 VAC
	Input Efficiency	87.8 % at 115 VAC and 88.5 % at 230VAC
	Input frequency range	50~ 60 Hz
	Input AC current	Max. 1.4 A at 90 VAC
	Output	
	Output power	45W
	DC output	19.5V
	Hold-up time	5ms at 115 Vac input
	Output current limit	The power supply shall limit the maximum steady state output current to an average current of 8 Amperes.
	Connector	4.5mm Barrel Type
	Environmental Design	
	Operating temperature	32°F to 95°F (0°C to 35° C)
	Non-operating (storage) temperature	-4°F to 185°F (-20°C to 85°C)
	Altitude	-4°F to 185°F (-20°C to 85°C)
	Humidity	The power supply can be operated at 5,000 m above sea level

Technical Specifications

HP 65 W Smart AC adapter (EM)	EMI and Safety Certifications	Storage Humidity *CE Mark – full compliance with LVD and EMC directives * Worldwide safety standards – IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals – C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE. * MTBF – over 200,000 hours at 25°C ambient condition.	
	Dimensions (H x W x D)	102 x 55 x 30mm	
	Weight	270 g	
	Input	100 to 240 VAC	
	Output	Input Efficiency	88.0 % at 115 VAC and 89.0 % at 230VAC
		Input frequency range	50~ 60 Hz
		Input AC current	Max. 1.7 A at 90 VAC
		Output power	65W
		DC output	19.5V
		Hold-up time	5ms at 115 Vac input
		Output current limit	The power supply shall limit the maximum steady state output current to an average current of 11 Amperes.
	Connector	4.5mm Barrel Type,	
	Environmental Design	Operating temperature	32°F to 95°F (0°C to 35° C)
HP 3-cell Li-Ion Long Life - Fast Charge (41 WHr)	EMI and Safety Certifications	Non-operating (storage) temperature	-4°F to 185°F (-20°C to 85°C)
		Altitude	The power supply can be operated at 5,000 m above sea level
		Humidity	The power supply shall withstand without degradation with 95% relative humidity, non-condensing, both operating and non-operating.
		Storage Humidity	
		*CE Mark – full compliance with LVD and EMC directives	
		* Worldwide safety standards – IEC60950, EN60950, UL60950, Class1, SELV; Agency approvals – C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCC, NOM-1 NYCE.	
		* MTBF – over 200,000 hours at 25°C ambient condition.	
	Dimensions (H x W x L)	6.0 x 186.85 x 90.2 mm (0.236 x 7.35 x 3.55 inch)	
	Weight	0.18 kg (0.39 lb)	
	Cells/Type	3cell Lithium-Ion Polymer cell / 515974	
	Voltage	11.4V	
	Amp-hour capacity	3.6Ah	
	Watt-hour capacity	41Wh	
	Operating (Charging)	32° to 113° F (0° to 45° C)	
	Operating (Discharging)	14° to 122° F (-10° to 60° C)	
	Optional Travel Battery Available	No	

Technical Specifications

HP 3-cell Li-Ion Long Life - Fast Charge (41 WHr)	Dimensions	6.0 x 186.85 x 90.2 mm (0.236 x 7.35 x 3.55 inch)
	Weight	0.19 kg (0.41 lb)
	Cells/Type	3cell Lithium-Ion Prismatic cell / 496080
	Voltage	11.55V
	Amp-hour capacity	3.615Ah/3.63Ah
	Watt-hour capacity	41Wh
	Operating (Charging)	32° to 113° F (0° to 45° C)
	Operating (Discharging)	14° to 122° F (-10° to 60° C)
	Optional Travel Battery Available	No

Options and Accessories (sold separately and availability may vary by country)

Category	Description	Part Number
Cases	HP Essential Top Load Case	H2W17AA#xxx
	HP Essential Backpack (up to 15.6")	H1D24AA
	HP Essential Messenger Case (up to 17.3")	H1D25AA
Docking	HP 3005PR USB3 Port Replicator	Y4H06AA
	HP USB Travel Dock	T0K30AA
Input/Output	HP Slim USB Keyboard and Mouse	T6T83AA
	HP Slim Wireless Keyboard and Mouse	T6L04AA
	HP 3-Button USB Laser Mouse	H4B81AA
	HP USB Travel Mouse	G1K28AA
	HP Comfort Grip Wireless Mouse	H2L63AA
	HP Ultra Mobile Wireless Mouse	H6F25AA#xxx
	HP HDMI to DVI Adapter	F5A28AA
Power	HP 45W Smart AC Adapter 4.5mm	H6Y88AA#XXX
	HP 65W Smart AC Adapter	H6Y89AA#xxx
	HP 65W Slim AC Adapter	H6Y82AA#xxx
Storage	HP External USB Optical Drive	F2B56AA
Memory	HP 4GB 2666Mhz DDR4	4VN05AA
	HP 8GB 2666Mhz DDR4	4VN06AA
UCC	HP Stereo USB Headset	T1A67AA
	HP Stereo 3.5mm Headset	T1A66AA
	HP UC Wired Headset	K7V17AA
Displays	HP S140u 14-inch Portable Display	G8R65AA
	HP ProDisplay P223 21.5-inch Monitor	X7R61AA
	HP ProDisplay P232 23-inch Monitor	K7X31AA
	HP ProDisplay P240va 23.8-inch Monitor	N3H14AA
	HP EliteDisplay S14 14-inch USB-C Portable Monitor	3HX46AA

Summary of Changes

Date of change:	Version History:		Description of change:
March 1, 2019	From v1 to v2	Removed	USB-C Travel Dock
March 4, 2019	From v2 to v3	removed	Battery Life
March 25, 2019	From v3 to v4	Added	Battery Life
May 17, 2019	From v4 to v5	Updated	Battery Life
June 13, 2019	From v5 to v6	Updated	EPEAT
July 2, 2019	From v6 to v7	Updated	Battery Life
July 5, 2019	From v7 to v8	Updated	Color Gamut
September 6, 2019	From v8 to v9	Updated	i5-8265U and i7-8565U Processors

Copyright © 2019 Hewlett Packard Development Company, L.P.

The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel, Core and Celeron are trademarks of Intel Corporation in the U.S. and/or other countries. Bluetooth is a trademark of its proprietor used by HP Inc. under license. ENERGY STAR is a registered trademark owned by the U.S. Environmental Protection Agency.