

ThinkCentre M725 SFF Platform Specifications

Product Specifications Reference (PSREF)

Processor	AMD A6 / A8 / A10 / A12 and Ryzen 3 / 5 / 7 series processor						Manageability	DASH 10/1.1
	Processor	Cores / Threads	Frequency (Base/Max)	L2 Cache	Memory Support (Up to)	Integrated Graphics	Security chip	Discrete TPM 2.0, TCG Certified
							Security features	<ul style="list-style-type: none"> Security slot (in rear for optional Kensington® MicroSaver® cable) Padlock loop Smart USB protection, allows keyboard/mouse only, blocks all storage devices Optional cable lock to physically lock both keyboard and mouse Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Individual USB port disablement Optional chassis intrusion switch
	PRO A6-9500	2 / 2	3.5 / 3.8	1MB	DDR4-2400	Radeon R5	Keyboard	Some: Lenovo Calliope Keyboard (USB connector), black
	PRO A8-9600	4 / 4	3.1 / 3.4	2MB	DDR4-2400	Radeon R7		Some: Lenovo Traditional Keyboard (USB connector), black
	PRO A10-9700	4 / 4	3.5 / 3.8	2MB	DDR4-2400	Radeon R7		Some: Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black
	PRO A12-9800	4 / 4	3.8 / 4.2	2MB	DDR4-2400	Radeon R7		Some: Lenovo Keyboard (PS/2 connector), black (only available via special bid)
	Ryzen 3 2300X	4 / 4	3.5 / 4.0	2MB	DDR4-2933	None	Mouse	Some: Lenovo Calliope Mouse (USB connector), black
	Ryzen 5 2500X	4 / 8	3.6 / 4.0	2MB	DDR4-2933	None		Some: Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black
	Ryzen 3 PRO 2200G	4 / 4	3.5 / 3.6	2MB	DDR4-2933	Radeon Vega 8		Some: Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black
	Ryzen 5 PRO 2400G	4 / 8	3.6 / 3.8	2MB	DDR4-2933	Radeon RX Vega 11		Some: Lenovo Mouse (PS/2 connector), black (only available via special bid)
	Ryzen 5 PRO 2600	6 / 12	3.4 / 3.9	3MB	DDR4-2933	None		
	Ryzen 7 PRO 2700	8 / 16	3.2 / 4.1	4MB	DDR4-2933	None		
Memory	64GB max, UDIMM, DDR4-2666*, four 288-pin DIMM sockets, non-ECC, dual-channel capable * Systemboard supports up to DDR4-2666, memory frequency may automatically clocks down for the lower capability of memory controller in processor						Mechanical	<ul style="list-style-type: none"> SFF (8.4L), black color; metal case (WxDxH) 3.6" X 11.4" X 13.5"; 92.5mm X 290.5mm X 343.5mm Approx. 13.2 lb (6.0 kg), weight may vary by configuration Toolless cover, disk, optical removal Optional dust filter Optional system floor stand for vertical orientation
Storage	Some: Hard Drive / SATA 6.0Gb/s, 2.5" or 3.5", 5400 rpm or 7200 rpm Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Some: M.2 SSD / PCIe NVMe, PCIe 3.0 x 4*, 32Gb/s * 128GB SSD M.2 (2242) PCIe NVMe and AMD A6 / A8 / A10 / A12 processor only supports PCIe 3.0 x 2, 16Gb/s							<ul style="list-style-type: none"> Bay 1: Slim external ODD bay Bay 2: 3.5", internal, HDD/SSD Bay 3: 2.5", internal, HDD/SSD (bay only comes with 2.5" 2nd disk) Slot 1: low-profile (length < 150mm, height < 68mm), PCIe 3.0 x16 Slot 2: low-profile (length < 150mm, height < 68mm), PCIe 2.0 x1 Slot 3: low-profile (length < 150mm, height < 68mm), PCIe 2.0 x1 Slot 4: low-profile (length < 150mm, height < 68mm), PCI 3.0 M.2 card slots: two (one for WLAN, one for SSD)
Optical	Some: DVD-ROM SATA 1.5Gb/s Drive, slim (9.0mm) Some: DVD Burner (DVD±RW), SATA 1.5Gb/s Drive, slim (9.0mm)						Floor Stand	Optional system floor stand for vertical orientation
Onboard SATA	Three onboard SATA 6.0Gb/s connectors, RAID 0/1 support (RAID preset only available via special bid model)						Power supply	<ul style="list-style-type: none"> Some: 180 watts, autosensing, 85% PSU Some: 210 watts, autosensing, 85% PSU Some: 260 watts, autosensing, 92% PSU (only available via special bid)
Media reader	Optional 7-in-1 media reader						Limited warranty	1-year or 3-year, limited onsite service / service upgrades available
Graphics	AMD Radeon™ Graphics in processor (only for some processors), uses main memory, DirectX® 12, one VGA, two DisplayPort™ (Onboard VGA and DP ports are only available on the models with integrated graphics), supports 3 independent displays, works along with AMD discrete graphics to support more displays; Max resolution: 4096x2160 (DP)@60Hz; 1920x1200 (VGA)@60Hz Some: NVIDIA GeForce® GT 730, DirectX 12, 2GB GDDR5, PCIe 2.0 x16 (x8 elec.) adapter, two DisplayPort, 35 watts; Max resolution: 3840x2160 (DisplayPort)@60Hz						Preload	Preloaded operating system Some: Windows 10 Pro 64-bit Some: Windows 10 Home 64-bit Preloaded applications (only some listed) <ul style="list-style-type: none"> Lenovo Vantage Microsoft Office preloaded; purchase a product key to activate Cyberlink PowerDVD (only for models with DVD / DVD±RW) Cyberlink Power2GO (only for models with DVD±RW) LinkedIn
Monitor cable	Optional DP to VGA dongle, DP to DVI-D dongle, DP to dual DP dongle, or DP to HDMI 1.4 dongle						Environment	ENERGY STAR® 6.1*, EPEAT™ Gold rating* (*not for non-OS models); ErP Lot 3; RoHS-compliant
Chipset	AMD B450 Chipset						Accessories	For compatible accessories, please go to http://smartfind.lenovo.com
Front ports (Std.)	2x USB 3.1 Gen2, 2x USB 3.1 Gen1, 1x microphone (3.5mm), 1x headphone (3.5mm)							
Front ports (Opt.)	Optional: 1x media reader, 2x USB 3.1 Type-C Gen2 via PCIe card (special bid only)							
Rear ports (Std.)	2x USB 3.1 Gen1, 2x USB 2.0, 1x serial (9-pin), 1x ethernet (RJ-45), 1x VGA*, 2x DisplayPort*, 2x PS/2 ports (keyboard / mouse); 1x line-in (3.5mm), 1x line-out (3.5mm), 1x microphone (3.5mm) * only available on the models with integrated graphics							
Rear ports (Opt.)	Optional: 2x USB 2.0, 1x 2nd serial (9-pin), 1x parallel (25-pin), additional RJ-45 and video ports available on optional graphics or ethernet card							
Audio support	High Definition (HD) Audio, Realtek ALC662 / optional internal speaker (1 watt)							
WLAN	Some: 11ac wireless, M.2 Card, Realtek RTL8821CE (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Qualcomm Atheros QCA9377A (dual band), Wi-Fi + Bluetooth 4.2* combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Realtek RTL8822BE (dual band), Wi-Fi + Bluetooth 4.2* combo adapter, 2x2 Some: 11ac wireless, M.2 Card, Qualcomm Atheros QCA6174A (dual band), Wi-Fi + Bluetooth 4.2* combo adapter, 2x2							
Bluetooth™	Some: Bluetooth 4.2* wireless, integrated in Wi-Fi + BT combo adapter * Hardware supports BT 4.2, but Win10 RS3 and earlier only supports BT 4.1							
Ethernet	Gigabit ethernet, Realtek RTL8111EPV, Wake on LAN®							
Ethernet (Opt.)	Some: Bitland BN8E88, gigabit ethernet, 1x RJ-45, PCIe x1 (special bid only)							

Note: The specifications above may not be available in all regions.

Lenovo, July 2018