## ThinkPad T490 Platform Specifications

Processor	8th Gener	ation Ir	ntel® Cor	e™ i5 / i7 F	rocessor					Dimensions	<i>WxDxH:</i> 12.95" x 8.94" x 0.70"; 329mm x 227mm x 17.9mm					
	Processor	# of	# of	Base	Max Turbo	ache	Memory	Proces	ssor	Weight	Models	HD	FHD	FHD Low Power / WQHD	Privacy Guard	
	Number	Cores	Threads	Frequency	rrequericy		Types	Graph	nics		Weight	3.37 lb / 1.53 l	kg   3.41 lb / 1.55 kg	3.23 lb / 1.46 kg	3.56 lb / 1.61 kg	
	i5-8265U	4	8	1.6 GHz		6MB				Case color Case material	Black Display agyor: BBS / 50% CE:					
	i5-8365U i7-8565U			1.6 GHz 1.8 GHz		6MB 8MB	DDR4-2400	ntel UHD Graphics 620	Case material	Display cover: PPS / 50% GF; Bottom: PA / 50% GF						
	i7-8665U	1		1.9 GHz		8MB		020	,	Smart card reade						
		eneration	on Intel C		Processor (N		vailable in E	EMEA)		Media reader Ports	MicroSD card reader Two USB 3.1 Gen 1 (one Always On), one USB 3.1 Type-C Gen 1 (with the function of Power Delivery and DisplayPort),					
	Processor Number	# of	# of Threads	Base Frequency	Max Turbo Frequency	ache	Memory Types	Proces Graph		Ports						
	i5-10210LL			1.6 GHz		MR					one USB 3.1 Type-C Gen 2 / Thunderbolt 3 (with the function of PD and DP), HDMI 1.4b, Ethernet (RJ-45), nano-SIM card slot (WWAN models), headphone / microphone combo jack, optional smart card reader, micros D card reader, side decking compactor, security keybole.					
	i7-10510U	4	8	1.8 GHz	4.9 GHz	8MB	DDR4-2400	Intel UHD Graphics								
Graphics	Intel UHD Graphics 620 or Intel UHD Graphics in processor only or Intel UHD Graphics 620 or Intel UHD Graphics in processor and NVIDIA® GeForce® MX250, 2GB GDDR5 memory;									Manitan aabla	microSD card reader, side docking connector, security keyhole * Depending on many factors, actual data transfer speed may be lower than theoretical speed HDMI to VGA: Lenovo HDMI to VGA Monitor Adapter USB-C to VGA: Lenovo USB-C to VGA Adapter					
										Monitor cable (optional)						
	supports e	externa	l digital r	nónitor via	HDMI or Thu		oolt;			(op normal)	USB-C to HDMI: Lenovo USB-C to HDMI Adapter USB-C to DP: Lenovo USB-C to DisplayPort Adapter					
	supports t				; (Thunderbolt	· 400	asv2160@3		MIX	Bundled Accy						
Chipset	Intel SoC				`	), 403	70XZ 100 @ Z	24112 (11101	vii)	<u>'</u>	None al) One of the following, configurable by model:					
Memory	48GB max / 2400MHz DDR4, dual-channel capable, 8GB or 16GB memory soldered to systemboard, one DDR4 SO-DIMM socket									Carriora (optional	<ul> <li>HD720p camera with ThinkShutter camera privacy, fixed focus</li> </ul>					
					ystemboard, out run at 2400				<b>cet</b>	Audio support	<ul> <li>IR camera and HD720p camera with ThinkShutter camera privacy, fixed focus HD Audio, Realtek® ALC3287 codec /</li> </ul>					
Display			l detading		ĺ	Aspe			Viewing	∃ ''	stereo speakers, 2W x 2, Dolby® Audio™ Premium /					
	Size Reso			pe Surface	Brightness	Ratio	Ratio	Gamut	Angle					eadphone / microphone	combo jack	
	14.0" HD (1	1366x76	(8)	N Anti-gla		16:9	400:1	45%	90°	Keyboard UltraNav™				optional LED backlight s Mylar surface multi-tou	ch touchnad	
	14.0" FHD	(4000-4000)	000)	OC Antinio	250 nits (non-touch)	16:9	700:1	45%	170°	Security		TrackPoint® pointing device and buttonless Mylar surface multi-touch touchpad  Power-on password, hard disk password, supervisor password, security keyhole				
	14.0   FND	(1920)	920X 1080)	S Anti-glare	300 nits (multi-touch)		700.1	45%	170	Security chip	Discrete	TPM 2.0. TCC		ouporvioor pacerrora, oc	outry Roynolo	
	a FHD	(1920x1	080) .		1		200.4		4=00	System Mgt (opt)	Intel vPro	o Technology	notab on abin finas	rariat roader on the nels	n root	
	Low Power		·   I	PS Anti-gla	e 400 nits	16:9	800:1	72%	170°	NFC (optional)		ld Communica		erprint reader on the palr	ii rest	
	FHD 14.0" Think	(1920x1	080)	S Anti-glare	e 400 nits	16:9	1000:1	72%	170°	Battery	Integrate	d Li-ion 50Wh	battery, supports I	Rapid Charge (charge up	o to 80% in 1hr)	
	Guar		vacy 1	r o rana giai	400 11113	10.5	1000.1	12/6	170		with 65W AC adapter  MobileMark® 2014: 16.11 hr  * Battery life varies significantly with settings, usage, & other factors 45W, 65W, or 65W slim USB-C AC adapter					
		ID (2560 , Dolby \		S Glossy	ossy 500 nits	16:9	1500:1	100% Adobe	170°	Max battery life						
Multi-touch (opt)				n-finger ge	 sture (FHD o	nly)		Adobe		AC adapter						
Storage			• •		OT available		FA)			Operating system (optional)	n • Windov • Window	vs® 10 Home 6 vs 10 Pro 64	54			
Otorage	<ul> <li>M.2 228</li> </ul>	0 SSD	/ PCIe N	IVMe, PČI	€ 3.0 x 4		_,,,			(Optional)		vs 10 Pro in S	mode			
	• M.2 224	2 SSD	/ PCle N	IVMe, PCI	9 3.0 x 2	0 40 00				Limited warranty (optional)	One of the following, configurable by model:  1-year depot repair service  1-year depot with 2-year system board repair service  3-year/1-yr battery depot repair service					
	M.2 228	tane™ i 0. PCle	Nemory NVMe	пто with s 3.0 x 4	Solid State St	orage	,									
Optical	None	o, . o														
Ethernet	Non-vPro model: Intel Ethernet Connection I219-V (Jacksonville) vPro model: Intel Ethernet Connection I219-LM (Jacksonville)										• 1-year -	+ 2-year/1-yr b	attery limited onsit			
WLAN +	One of the	following	g, configu	able by mod	lel:			,		Mil-Spec test	3-year/1-yr battery limited onsite service     MIL-STD-810G military testing					
Bluetooth™	• Intel Wireless-AC 9560, Wi-Fi 2x2 802.11ac + Bluetooth 5.0									Environment	, ,			HS-compliant		
(optional)		<ul> <li>Intel Wi-Fi 6 AX201, Wi-Fi 2x2 802.11ax + Bluetooth 5.0 (AX201 for 10th Gen processor only)</li> </ul>														
WWAN (optional)		One of the following, configurable by model:														
	<ul> <li>Wireless WAN upgradable (special bid only in EMEA)</li> <li>Integrated Mobile Broadband 4G LTE, Fibocom L830-EB, M.2 card (EMEA only)</li> </ul>															
	<ul> <li>Integrate</li> </ul>	ed Mobi	ile Broad	lband 4G I	TE-A. Fiboco	m L8	50-GL. M.2	card								
	<ul> <li>Integrated Mobile Broadband 4G LTE-A, Fibocom L850-GL, M.2 card</li> <li>Integrated Mobile Broadband 4G LTE-A, Fibocom L860-GL, MIMO 4x4, M.2 card</li> <li>* For non-WWAN model, it means the model is NOT WWAN upgradable</li> </ul>															
SIM card (opt)	* For non-W	VWAN m	nodel, it m	eans the mo	odel is NOT WV n LTE (US) Sl	VAN u <sub>l</sub>	ogradable									
Note: The enecifier					, ,	oai	~								Lanava	