ThinkPad T495 Platform Specifications

Processor	AMD Ryzen™ PRO Mobile Processors with Radeon™ Vega Graphics										Dimensions	<i>WxDxH:</i> 12.95" x 8.94" x 0.70": 329mm x 227mm x 17.9mm				
	Processor	# of	_ # of			ax Turbo	Cache	Memory	Processor		Weight	Models	HD		FHD	FHD Low Power
			Threads	Frequency	ency Fre		2MB L2 /	Controller	Graphics			Weight	3.46 lb / 1.5	7 kg	3.46 lb / 1.57 kg	3.39 lb / 1.54 kg
	Ryzen 3 Pro 3300U 4		4	2.1 G	GHz 3.		4MB L3	DDR4-2400	Radeon Vega 6 Graphics Radeon Vega 8 Graphics		Case color Case material	Black Display cover: PPS / 50% GF; Bottom: PA / 50% GF				
	Ryzen 5 Pro 3500U 4		8	2.1 G	GHz 3.		MB L2 / 4MB L3				0					
	Ryzen 7 Pro 3700U 4		8	2.3 G	GHz 4.	0.04- 2	2MB L2 / 4MB L3		Radeon		Smart card reade Media reader Ports	er <i>Optional:</i> Smart card reader MicroSD card reader One USB 3.1 Gen 1 (Always On), one USB 3.1 Gen 2,				
	AMD Radeon Vega 6, Vega 8, or Vega 10 Graphics in processor; supports external digital monitor via USB-C or HDMI; supports four independent displays; Max resolution: 5120x2880@60Hz (USB-C); 4096x2160@60Hz (HDMI)											two USB 3.1 Type-C Gen 2 (with the function of Power Delivery and DisplayPort HDMI 2.0, Ethernet (RJ-45), nano-SIM card slot (WWAN models), headphone / microphone combo jack, optional smart card reader, microSD card reader, side docking connector, security keyhole *Depending on many factors, actual data transfer speed may be lower than theoretical spee				
Memory	AMD SoC 32GB max 8GB or 16 * Installed r	x / 240 SGB m	0MHz D emory so	DŘ4, o oldere	dual-cha d to syst	temboard	d, one D	DR4 SO-DII ue to AMD lim	MM sock	ĸet	Monitor cable (optional) Bundled Accy	HDMI to VGA: Lenovo HDMI to VGA Monitor Adapter USB-C to VGA: Lenovo USB-C to VGA Adapter USB-C to DP: Lenovo USB-C to DisplayPort Adapter None				
Display	Size Reso	7	Гуре Ѕ	Surface	Brightnes	s Aspec	ct Contrast Ratio		Viewing Angle	Camera (optional	One of the following, configurable by model: HD720p camera with ThinkShutter camera privacy, fixed focus					
	14.0" HD (1366x76	68)	TN Ar	nti-glare	220 nits	16:9	400:1	45%	90°	1	• IR came	era and HD7	20p ca	amera with Think	Shutter camera privacy, fixed focus
	14.0" FHD (1920x1080		1080)	IPS Anti-gla		250 nits (non-toucl 300 nits (multi-touc	ⁿ⁾ 16:9	700:1	45%	170°	Audio support	HD Audio, Realtek® ALC3287 codec / stereo speakers, 2W x 2, Dolby® Audio™ Premium / dual array far-field microphone, headphone / microphone combo jack 6-row, spill-resistant, multimedia Fn keys, optional LED backlight				
		(1920x	1080)	IPS Ar	nti-glare	400 nits	1	800:1	72%	170°	Keyboard UltraNav™					otional LED backlight Nylar surface multi-touch touchpad
Multi-touch (opt)	On-cell to	uch, sı	upports 1	10-fing	er gestu	ıre (FHD	only)			1	Security Security chip	Power-on password, hard disk password, supervisor password, security keyhole				
Storage	• M.2 2280 SSD / SATA 6.0Gb/s										System Mgt	Discrete TPM 2.0, TCG Certified DASH Management				
	 M.2 2280 SSD / PCIe NVMe, PCIe 3.0 x 4 M.2 2242 SSD / PCIe NVMe, PCIe 3.0 x 2 										Fingerprint reade NFC	r Optional: Touch style match on chip fingerprint reader on the palm rest None				
-	None										Battery	Integrated Li-ion 50Wh battery, supports Rapid Charge (charge up to 80% in				pid Charge (charge up to 80% in 1hr)
	Realtek® RTL8111 Gigabit Ethernet connection Intel Wireless-AC 9260. Wi-Fi 2x2 802.11ac + Bluetooth 5.0										Max battery life		with 65W AC adapter MobileMark® 2014: 13.4 hr			
	Bluetooth 5.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter										AC adapter	* Battery life varies significantly with settings, usage, & other factors 45W or 65W USB Type-C AC adapter				
	One of the following, configurable by model: • Wireless WAN upgradable • Integrated Mobile Broadband 4G LTF-A Fibocom I 850-GL M 2 card										Operating system		71			64
											Limited warranty					
	 Integrated Mobile Broadband 4G LTE-A, Fibocom L850-GL, M.2 card *For non-WWAN model, it means the model is NOT WWAN upgradable Nano-SIM card slot, optional Verizon LTE (US) SIM card 											• 1-year	depot repair s 1-yr battery d		e repair service	
											Mil-Spec test	MIL-STD-810G military testing				
											Environment	EPEAT™	Silver; ENEF	RGY S	STAR® 7.1; RoHS	-compliant

Note: The specifications above may not be available in all regions.