ThinkPad T580 Platform Specifications

Processor	7th Generation Intel® Core™ i5 Processor		Dimensions WxDxH: 14.40" x 9.95" x 0.79-0.80"; 365.8mm x 252.8mm x 19.95-20.2mm	
	Processor # of # of Base Max Turbo Cache Memory	FIUCESSUI	Weight	Integrated model: starting at 4.29 lb / 1.95 kg; Discrete model: starting at 4.39 lb / 1.99 kg
	Number Cores Threads Frequency Frequency Types	Graphics	Case color	Black
	i5-7300U ² ⁴ 2.6 GHz 3.5 GHz 3MB DDR4-2133	el HD Graphics 620	Case material	Display cover: GFRP + PPS; Bottom: GFRP
	or 8th Generation Intel Core i5 / i7 Processor		Smart card reader Optional: Smart card reader	
	Processor # of # of Number Cores Threads Frequency Frequency Cache Types		Media reader Ports	4-in-1 reader (MMC, SD, SDHC, SDXC) Two USB 3.1 Gen 1 (one Always On), Very State of Payer Politicary and Display Both
	1.6 GHz 3.4 GHz 6MB 1.7 GHz 3.6 GHz 6MB 1.7 GHz 3.6 GHz 6MB 1.8 GHz 4.0 GHz 8MB 1.9 GHz 4.2 GHz 1.0 GHz	el UHD Graphics 620		one USB 3.1 Type-C Gen 1 (with the function of Power Delivery and DisplayPort), one USB 3.1 Type-C Gen 2 / Thunderbolt 3 (with the function of PD and DP), HDMI 1.4b, Ethernet (RJ-45), nano-SIM card slot (WWAN models), headphone / microphone combo jack, optional smart card reader, 4-in-1 reader (MMC, SD, SDHC, SDXC), side docking connector, security keyhole
Graphics	Intel HD Graphics 620 or Intel UHD Graphics 620 in processor only or Intel HD Graphics 620 or Intel UHD Graphics 620 in processor and NVIDIA® GeForce® MX150, 2GB GDDR5 memory; supports external digital monitor via HDMI or USB Type-C; supports three independent displays; Max resolution: 4096x2304@60Hz (USB Type-C); 4096x2160@30Hz (HDMI) Intel SoC (System on Chip) platform 32GB max / 2400MHz DDR4, dual-channel capable, two DDR4 SO-DIMM sockets * System clocks down for processors with lower memory controller		Monitor cable (optional)	* Depending on many factors, actual data transfer speed may be lower than theoretical speed HDMI to VGA: Lenovo HDMI to VGA Monitor Adapter USB-C to DP: Lenovo USB-C to DisplayPort Adapter
			Camera (optional) One of the following, configurable by model:	
-			Audio support	HD720p camera with ThinkShutter camera privacy, fixed focus IR camera and HD720p camera, fixed focus HD Audio, Realtek® ALC3287 codec / stereo speakers, 2W x 2, Dolby® Audio™ Premium / dual array microphone, headphone / microphone combo jack
Chipset Memory				
Display	Some: 15.6" (396mm) FHD (1920x1080), anti-glare, LED backlight, I 250 nits, 16:9 aspect ratio, 700:1 contrast ratio, 170° viewing a	FHD (1920x1080), anti-glare, LED backlight, IPS, aspect ratio, 700:1 contrast ratio, 170° viewing angle		6-row, spill-resistant, multimedia Fn keys, numeric keypad, optional LED backlight TrackPoint® pointing device and buttonless Mylar surface multi-touch touchpad
Multi-touch (opt)	Some: 15.6" (396mm) ÚHD (3840x2160), anti-glare, LED backlight, IPŠ, 300 nits, 16:9 aspect ratio, 1000:1 contrast ratio, 72% gamut, 170° viewing angle On-cell touch, supports 10-finger gesture (FHD only)		Security Power-on password, hard disk password, supervisor password, security keyhole Security chip Discrete TPM 2.0, TCG Certified vPro (optional) Intel vPro Technology Fingerprint reader Optional: Touch style match on chip fingerprint reader on the palm rest,	
Storage	System has one HDD slot or one M.2 2280 slot exclusively for storage			
Storage	Some: HDD / SATA 6.0Gb/s, 2.5" wide, 7mm high, Active Protection System™		NFC (optional)	anti-spoofing technology Near Field Communication
	Some: SSD / SATA 6.0Gb/s, 2.5" wide, 7mm high (e.g. xxxGB SSD) Some: M.2 SSD / PCle NVMe, PCle 3.0 x 2, 16Gb/s Some: 128GB M.2 SSD / PCle NVMe, PCle 3.0 x 2, 16Gb/s, in WWAN slot as 2nd Storage, mutually exclusive with WWAN emory Optional: Intel Optane memory, PCle NVMe, PCle 3.0 x 2 None		Battery	Optional integrated Li-ion 32Wh battery and
			,	external Li-ion 24Wh, 48Wh, or 72Wh battery
Optane™ memory Optical			Max battery life (MobileMark® 2014)	Models 24Wh 48Wh 72Wh 32Wh + 24Wh 32Wh + 48Wh 32Wh + 72Wh Max battery life 5.8 hr 12.5 hr 18.1 hr 13.8 hr 20.3 hr 26.1 hr
Ethernet			AC adapter	* Battery life varies significantly with settings, usage, & other factors 45W or 65W USB Type-C AC adapter
WLAN +	ntel Dual Band Wireless-AC 8265, Wi-Fi 2x2 802.11ac + Bluetooth 4.1, M.2 card			Optional: Windows® 10 Home 64 or Windows 10 Pro 64
Bluetooth™	el 8265ac card supports BT4.2 but is limited to BT4.1 by Windows OS			One of the following, configurable by model: 1-year depot repair service
(-1	 Integrated Mobile Broadband 4G LTE, Intel XMM™ 7262 (Fibocom L830-EB), M.2 card (EMEA only) Integrated Mobile Broadband 4G LTE-A, Intel XMM™ 7360 (Fibocom L850-GL), M.2 card For non-WWAN model, it means the model is NOT WWAN upgradable 			 1-year depot with 2-year system board repair service 3-year/1-yr battery depot repair service 3-year/1-yr battery limited onsite service
			Mil-Spec test	MIL-STD-810G military testing
SIM card (opt)			Environment	EPEAT™ Silver; ENERGY STAR® 6.1; RoHS-compliant

Note: The specifications above may not be available in all regions.